

WiNG Range

GENERAL			
	AFU	DFU	DFU 3C
Acquisition	- Data filtering, compression & time stamping 24 bits A/D conversion	- Data filtering, compression & time stamping 24 bits data	
Sensor tests	resistance, noise, tilt	distortion, noise, tilt	distortion, noise, tilt, gravity
Instrument tests	noise, gain, phase, distortion	gain, phase, distortion	gain, phase, distortion, Xtalk
Memory autonomy	1480 hours (60 days 24 hr/day)		
Battery autonomy (Pathfinder enabled) (Pathfinder disabled)	960 hours (40 days 24 hr/7days) 1200 hours (50 days 24 hr/7days)		430 hours (18 days 24 hr/7days) 480 hours (20 days 24 hr/7days)
Weight	760 g	780 g (no spike), 830 g (with spike)	850 g

ENVIRONMENTAL LIMITS	
Operational temperature	-40 °C to +60 °C
Storage temperature	-40 °C to +60 °C
Ingress protection	IP68
Battery charge temperature	0 °C to +30 °C

RADIO TRANSMISSION -Pathfinder	
Frequency band	2402 MHz – 2478 MHz
Range	75 m nominal LOS


RADIO TRANSMISSION - Direct	
Frequency band	2402 MHz – 2478 MHz
Range	50 m nominal LOS

GNSS	
Supported constellations	GPS L1 C/A / SBAS / QZSS, GLONASS, BeiDou, Galileo
Cold start acquisition sensitivity	GPS, GLONASS: -148 dBm

SENSOR PARAMETERS


	AFU	DFU	DFU 3C
Sensor type	External	MEMS Accelerometer	
Sample rate	4, 2, 1, 0.5 ms		
Timing accuracy	Synchronous to gps clock < +/-5μs		
Input impedance differential mode	20 kΩ // 77 nF	-	
Bandwidth	-	0-400 Hz, 3 dB	
Low-cut filter	Selectable (none, 0.15625 Hz, 0.3125 Hz, 0.625 Hz, 1.25 Hz, 2.5 Hz)		
High-cut filter	0.8 FN linear or minimum phase		
Full scale	1.6 V RMS (0 dB), 400 mV RMS (12 dB), 100 mV RMS (24 dB) (pre-amp gain)	5 m/s² (510 mg)	
Noise (3-200Hz)	350 nV RMS(0 dB), 145 nV RMS (12 dB), 90 nV RMS (24 dB)	-	
Noise (10-200Hz)	-	0.15 μm/s2/√Hz (15 ng/√Hz)	
Instantaneous dynamic range	132 dB	128 dB	
System dynamic range	145 dB	-	
Distortion	-110 dB	-90 dB	
Gain accuracy	< 0.1 %	< 0.25 %	
Phase accuracy	< 20 μs	< 5 μs	< 5 μs
Orthogonality accuracy	-	-	+/-0.25°
Tilt measurement accuracy	-	-	+/-0.5°

Note: Azimuth tool (compass) required at deployment for proper 3C acquisition and data processing




RACK

Dimensions	2075 mm H x 600 mm W x 300 mm D without shock absorbers 2200 mm H x 600 mm W x 630 mm D with shock absorbers and screen
Weight	130 Kg
Capacity	36 slots
Charging time	6 hr (fully discharged – fully charged)
Input voltage	110-240 Vac
Rated power	950 W (with 36xDFU charging)
Operational temperature	0 °C to +30 °C
Storage temperature	-40 °C to +70 °C
Charge temperature	0 °C to +30 °C
Protection rating	IP4X




PORTABLE HARVESTER CHARGER


Dimensions	682x777x771 mm
Weight	65 Kg
Capacity	12 slots
Charging time	6 hr (fully discharged – fully charged)
Input voltage	110-240 Vac
Rated power	325 W (with 12xDFU charging)
Operational temperature	0 °C to +30 °C
Storage temperature	-40 °C to +70 °C
Charge temperature	0 °C to +30 °C
Protection rating	IP54 closed / IP4X open



System architecture: WiNG




System architecture: WiNG Lite



FIELD MONITOR

FIELD MONITOR BOX

Dimensions	152 mm (6") x 110 mm (4.33") x 47 mm (1.85")
Weight	565 g
Charging time	3 hrs (fully discharged – fully charged)
Input voltage	5 V (USB) – (230 Vac / 5 V 2 A for USB Charger)
Radio GFSK	Direct Frequency band 2402 MHz – 2478 MHz
WIFI	2.4 GHz : 802.11 g 5 GHz : 802.11 an
Operational temperature	-20 °C to +60 °C
Storage temperature	-40 °C to +60 °C
Charge temperature	0 °C to +30 °C
Protection rating	IP67
Battery autonomy	Up to 10 h



FIELD MONITOR DEVICE

Type	Tablet 8"
Dimensions	210 mm (8.3") x 124.4 mm (4.9") x 8.0 mm (0.31")
Weight	345 g
Protection rating	IP68
Battery autonomy	Up to 10 h

Note: Sercel reserves the right to change its specifications without prior notice.
All specifications are typical at 25 °C, 2 ms sampling except where otherwise stated

SERCEL - FRANCE

16 rue de Bel Air - B.P. 30439 - 44474 CARQUEFOU Cedex
Téléphone : (33) 2 40 30 11 81
E-mail : sales.nantes@sercel.com
SAS au capital de 25 000 000 €
Siège Social : 16 rue de Bel Air - 44470 CARQUEFOU
378.040.497 R.C.S. Nantes Code APE 2651B

SERCEL INC. - U.S.A.

17300 Park Row
Houston, Texas 77084
Telephone : (1) 281 492 6688
E-mail : sales.houston@sercel.com

sercel.com